

SAFETY DATA SHEET

Gulf Gear DB, SAE 85W-90

03105/85W-90/1

Issuing Date: 08-16-2016

Revision Date: 08-16-2016

Version 2

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product NameGulf Gear DB, SAE 85W-90Product Code(s):03105/85W-90/1

1.2. <u>Relevant identified uses of the substance or mixture and uses advised against</u>

Recommended use Transmission Oil

Uses advised against Any other purpose.

1.3. Details of the supplier of the safety data sheet

Supplier

Gulf Oil Supply Company Limited B2 Industry Street, Qormi, QRM 3000, Malta +44 207 321 6219 products@gulfoilltd.com sds@gulfoilltd.com

1.4. Emergency telephone number

Europe (+) 44 808 189 0979 Code 334276 (+) 1 760 476 3961 Code 334276 (+) 32 (0) 3241 33 55

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Chronic aquatic toxicity

Category 3 - (H412)

2.2. Label Elements

Signal Word None

Hazard Statements

H412 - Harmful to aquatic life with long lasting effects

Precautionary Statements - EU (§28, 1272/2008)

P273 - Avoid release to the environment

P501 - Dispose of contents/ container to an approved waste disposal plant

2.3. Other hazards

No information available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances / 3.2. Mixtures

This product is a mixture. Health hazard information is based on its ingredients

Chemical Name	EC-No	CAS-No	Weight %	Classification (Reg. 1272/2008)	REACH Registration Number
Highly refined base oil (Viscosity >20.5 cSt @40°C)	-	-	50% - 100%	**	-
Methacrylate copolymer	-	NOT AVAILABLE	1% - 2.5%	Eye Irrit. 2 (H319)	no data available
Alkyl dithiophosphate	-	NOT AVAILABLE	0% - 1%	Eye Irrit. 2 (H319) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410)	no data available

Additional information

Product containing mineral oil with less than 3% DMSO extract as measured by IP 346 See Section 15 for additional information on base oils.

** Substances for which there are Community workplace exposure limits

Full text of H- and EUH-phrases: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of first-aid measures

General advice	If symptoms persist, call a physician.	
Inhalation	Move to fresh air.	
Skin contact	Wash off immediately with soap and plenty of water. Remove and wash contaminated clothing before re-use.	
Eye contact	Rinse thoroughly with plenty of water, also under the eyelids. Keep eye wide open while rinsing.	
Ingestion	Clean mouth with water. Drink plenty of water. Do not induce vomiting without medical advice.	
Protection of First-aiders	Use personal protective equipment.	
4.2. Most important symptoms and	effects, both acute and delayed	
Main Symptoms	None	
4.3. Indication of immediate medical attention and special treatment needed		
Notes to physician	Treat symptomatically.	

SECTION 5: FIRE FIGHTING MEASURES

5.1. Extinguishing media

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment:, Use CO2, dry chemical, or foam, Water spray or fog, Cool containers / tanks with water spray

Extinguishing media which shall not be used for safety reasons

Do not use a solid water stream as it may scatter and spread fire

5.2. Special hazards arising from the substance or mixture

Special Hazard

Water runoff can cause environmental damage. Thermal decomposition can lead to release of irritating gases and vapors. Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke). In the event of fire and/or explosion do not breathe fumes. This material creates a fire hazard because it floats on water. Combustible material.

Hazardous Decomposition Products

Incomplete combustion and thermolysis produces potentially toxic gases such as carbon monoxide and carbon dioxide

5.3. Advice for firefighters

Special protective equipment for fire-fighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Ensure adequate ventilation. Use personal protective equipment. Avoid contact with skin, eyes and clothing.

Advice for non-emergency Material can create slippery conditions.

personnel

Advice for emergency responders For personal protection see section 8.

6.2. Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system. Prevent product from entering drains. Local authorities should be advised if significant spillages cannot be contained.

6.3. Methods and materials for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Dike to collect large liquid spills.

6.4. <u>Reference to other sections</u>

See Section 8/12/13 for additional information

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Ensure adequate ventilation. Do not eat, drink or smoke when using this product. Handle in accordance with good industrial hygiene and safety practice. Wear personal protective equipment. Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures/Storage conditions

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from open flames, hot surfaces and sources of ignition.

Incompatible Materials

Oxidizing agents

7.3. Specific end uses

Recommended use

Transmission Oil

STEL: 10 mg/m3

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

(Viscosity >20.5 cSt @40°C)

Chemical Name	European Union	United Kingdom	France	Spain
Highly refined base oil	-			VLA-EC: 10 mg/m ³
Viscosity >20.5 cSt @40°C)				VLA-ED: 5 mg/m ³
Chemical Name	Germany	Italy	Portugal	The Netherlands
Highly refined base oil		TWA: 5 mg/m ³	TWA: 5 mg/m ³	TWA: 5 mg/m ³
(Viscosity >20.5 cSt @40°C)			STEL: 10 mg/m ³	-
Chemical Name	Austria	Switzerland	Poland	Ireland
Highly refined base oil			TWA: 5 mg/m ³	STEL: 10 mg/m ³
(Viscosity >20.5 cSt @40°C)			STEL: 10 mg/m ³	TWA: 5 mg/m ³
			-	(Mist)
Chemical Name	Finland	Denmark	Norway	Sweden
Highly refined base oil (Visc	osity TWA: 5mg/m ³ (Öljys	umu) TWA: 1 mg/m ³ (Olietåge)	TWA: 1 mg/m ³ (Oljetåke)	LLV: 1 mg/m ³
>20.5 cSt @40°C)		, , , ,	, , , ,	STV: 3 mg/m ³
C ,				(Oljedimma)
			· · · ·	
Chemical Name	Czech Republic	Hungary	Bulgaria	Romania
Highly refined base oil	TWA: 5 mg/m ³	TWA: 5 mg/m ³	TWA: 5 mg/m ³	TWA: 5 mg/m ³
(Viscosity >20.5 cSt @40°C)	Ceiling: 10 mg/m ³		Ũ	STEL: 10 mg/m ³
		· · · · · ·	· · ·	
Chemical Name	Greece	Cyprus	Turkey	Malta
Highly refined base oil	TWA: 5 mg/m ³			
(Viscosity >20.5 cSt @40°C)	Ũ			
Chemical Name	Belgium	Luxembourg	Iceland	Croatia
Chemical Name	Deigium	Euxembourg	loolalla	oround
Highly refined base oil	TWA: 5 mg/m ³	Euxembourg	loolalla	eround

03105/85W-90/1 - Gulf Gear DB, SAE 85W-90

Chemical Name	Russia	Estonia	Latvia	Lithuania
Highly refined base oil			TWA: 5 mg/m ³	TWA: 1 mg/m ³
(Viscosity >20.5 cSt @40°C)			_	STEL: 3 mg/m ³

Chemical Name	Belarus	Ukraine	Slovakia	Slovenia
Highly refined base oil			TWA: 5mg/m ³	
(Viscosity >20.5 cSt @40°C)			_	

Derived No Effect Level (DNEL)

Workers Systemic toxicity

Workers Local effects

Consumers Systemic toxicity

Consumers Local effects

Predicted No Effect Concentration (PNEC)

8.2. Exposure controls

Engineering Measures	Ensure adequate ventilation, especially in confined areas.
Personal protective equipment Eye Protection Hand Protection	Safety glasses with side-shields. Protective gloves. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.
Skin and body protection Respiratory protection	Long sleeved clothing. No special protective equipment required. In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit.
Hygiene measures	Regular cleaning of equipment, work area and clothing is recommended.
Environmental Exposure Controls Thermal hazards	Do not allow material to contaminate ground water system. None under normal use conditions

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical state @20°C	liquid	Appearance		ar amber
Odor	Hydrocarbon-like	Odor Threshold		t Applicable
<u>Property</u> pH Melting Point / Freezing Point Boiling point/boiling range Flash point	<u>Values</u> No information available No information available No information available 210 °C / 410 °F		<u>Note</u> ASTM D 92	

03105/85W-90/1 - Gulf Gear DB, SAE 85W-90

No information available	
No information available	
No information available	
0.9006	@15°C
Insoluble in water	
No information available	
No information available	
156.9 cSt @ 40 °C	ASTM D 445
Not Applicable	
Not Applicable	
16.54 cSt @ 100°C -30 °C / -22 °F No information available No information available	ASTM D 445 ASTM D 97
	No information available No information available No information available No information available No information available 0.9006 Insoluble in water ter Not Applicable No information available 156.9 cSt @ 40 °C Not Applicable Not Applicable Not Applicable

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

None under normal use conditions

10.2. Chemical stability

Stable under normal conditions

10.3. Possibility of hazardous reactions

None under normal use conditions

10.4. Conditions to avoid

Heat, flames and sparks, Keep away from open flames, hot surfaces and sources of ignition

10.5. Incompatible Materials

Oxidizing agents

10.6. Hazardous decomposition products

Incomplete combustion and thermolysis produces potentially toxic gases such as carbon monoxide and carbon dioxide.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Product Information - Principle Routes of Exposure

Inhalation None known

Eye contact None known

03105/85W-90/1 - Gulf Gear DB, SAE 85W-90

Skin contact	None known
Ingestion	None known

Acute toxicity - Product Information

Product does not present an acute toxicity hazard based on known information.

Acute toxicity - Component Information

Chemical Name	LD50 Oral (Rat)	LD50 Dermal (Rat/Rabbit)	LC50 Inhalation
Highly refined base oil (Viscosity >20.5 cSt @40°C)	>2000 mg/kg	>2000 mg/kg	
Skin corrosion/irritation	Based on available data, t	he classification criteria are not n	net.
Serious eye damage/eye irritat	ion Based on available data, t	he classification criteria are not n	net.
Sensitization Respiratory Sensitization Skin sensitization		he classification criteria are not m he classification criteria are not m	
Germ Cell Mutagenicity	Based on available data, t	he classification criteria are not n	net.
Carcinogenicity	Based on available data, t	he classification criteria are not n	net.
Reproductive toxicity	Based on available data, t	he classification criteria are not n	net.
Specific target organ systemic toxicity (single exposure)	Based on available data, t	he classification criteria are not n	net
Specific target organ systemic toxicity (repeated exposure)	Based on available data, t	he classification criteria are not n	net
Aspiration hazard	Based on available data, t	he classification criteria are not n	net.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment

Aquatic toxicity H412 - Harmful to aquatic life with long lasting effects

12.2. Persistence and degradability

The product is not readily biodegradable, but it can be degraded by micro-organisms, it is regarded as being inherently biodegradable.

12.3. Bioaccumulative potential

No information available

12.4. Mobility in soil

The product is insoluble and floats on water

12.5. Results of PBT and vPvB assessment

This preparation contains no substance considered to be persistent, bioaccumulating nor toxic (PBT). This preparation contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

12.6. Other adverse effects

None known

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from Residues / Unused Products	Dispose of as hazardous waste in compliance with local and national regulations
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal. Observe all label precautions until container is cleaned, reconditioned or destroyed.
Other Data	According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user based on the application for which the product was used.

SECTION 14: TRANSPORT INFORMATION

14.1. UN-Number

Not regulated

14.2. UN proper shipping name

Not regulated

14.3. Transport hazard class

Not regulated

14.4. Packing group

Not regulated

14.5. Environmental Hazards

None

14.6. Special precautions for users

None

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

IMDG/IMO	Not regulated
ADR/RID	Not regulated
IATA_	Not regulated
ADN	Not regulated

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

The Classification, Labeling and Packaging of Substances and Mixtures (CLP) Regulation (EC 1272/2008) Registration, Evaluation, Authorization, and Restriction of Chemicals (REACh) Regulation (EC 1907/2006)

WGK Classification

Low hazard to water/Class 1

The highly refined base oil (Viscosity >20.5 cSt @40°C) contains one or more substance with the following CAS/EC numbers/REACH registration numbers:

Chemical Name	CAS-No	EC-No	REACH Registration Number
Distillates (petroleum), solvent-refined heavy paraffinic	64741-88-4	265-090-8	01-2119488706-23-xxxx
Distillates (petroleum), solvent-refined light paraffinic	64741-89-5	265-091-3	01-2119487081-40-xxxx
Residual oils (petroleum), solvent deasphalted	64741-95-3	265-096-0	01-2119487081-40-xxxx
Distillates (petroleum), solvent-refined heavy naphthenic	64741-96-4	265-097-6	01-2119483621-38-xxxx
Distillates (petroleum), solvent-refined light naphthenic	64741-97-5	265-098-1	01-2119480374-36-xxxx
Residual oils (petroleum), solvent-refined	64742-01-4	265-101-6	01-2119488707-21-xxxx
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	265-155-0	01-2119467170-45-xxxx
Distillates (petroleum), hydrotreated light naphthenic	64742-53-6	265-156-6	01-2119480375-34-xxxx
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	265-157-1	01-2119484627-25-xxxx
Distillates (petroleum), hydrotreated light paraffinic	64742-55-8	265-158-7	01-2119487077-29-xxxx
Distillates (petroleum), solvent-dewaxed light paraffinic	64742-56-9	265-159-2	01-2119480132-48-xxxx
Residual oils (petroleum), hydrotreated	64742-57-0	265-160-8	01-2119489287-22-xxxx
Lubricating oils (petroleum), hydrotreated spent	64742-58-1	265-161-3	
Residual oils (petroleum), solvent-dewaxed	64742-62-7	265-166-0	01-2119480472-38-xxxx
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	265-169-7	01-2119471299-27-xxxx
Paraffin oils (petroleum), catalytic dewaxed heavy	64742-70-7	265-174-4	01-2119487080-42-xxxx
Paraffin oils (petroleum), catalytic dewaxed light	64742-71-8	265-176-5	01-2119485040-48-xxxx
Lubricating oils (petroleum), C>25, hydrotreated bright stock-based	72623-83-7	276-735-8	
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, high-viscosity	72623-85-9	276-736-3	01-2119555262-43-xxxx
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	72623-86-0	276-737-9	01-2119474878-16-xxxx
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	72623-87-1	276-738-4	01-2119474889-13-xxxx
Lubricating oils	74869-22-0	278-012-2	01-2119495601-36-xxxx
White mineral oil (petroleum)	8042-47-5	232-455-8	

15.2. Chemical Safety Assessment

No information available

SECTION 16: OTHER INFORMATION

Key or legend to abbreviations and acronyms used in the safety data sheet

Repr.-Reproduction toxicity Asp. Tox. - Aspiration Toxicity Acute Tox. - Acute Toxicity Aquatic Acute - Acute Aquatic Toxicity Aquatic Chronic - Chronic Aquatic Toxicity Eye Dam. - Eye Damage Eye Irrit. - Eye Irritation Skin Corr. - Skin Corrosion Skin Irrit. - Skin Irritation Skin Sens. - Skin Sensitizer Resp. Sens. - Respiratory Sensitizer STOT SE - Specific target organ systemic toxicity (Single exposure) STOT RE - Specific target organ systemic toxicity (repeated exposure) VOC - Volatile organic compounds

Full text of H-Statements referred to under sections 2 and 3

 H224 - Extremely flammable liquid and vapor 	 H341 - Suspected of causing genetic defects 	
 H225 - Highly flammable liquid and vapor 	• H350 - May cause cancer	
H226 - Flammable liquid and vapor	 H351 - Suspected of causing cancer 	
 H270 - May cause or intensify fire; oxidizer 	 H360 - May damage fertility or the unborn child 	
 H271 - May cause fire or explosion; strong oxidizer 	 H361 - Suspected of damaging fertility or the unborn child 	
 H272 - May intensify fire; oxidizer 	 H362 - May cause harm to breast-fed children 	
H290 - May be corrosive to metals	 H370 - Causes damage to organs 	
H300 - Fatal if swallowed	 H371 - May cause damage to organs 	
H301 - Toxic if swallowed	 H372 - Causes damage to organs through prolonged or repeated 	
H302 - Harmful if swallowed	exposure	
 H304 - May be fatal if swallowed and enters airways 	 H373 - May cause damage to organs through prolonged or repeated 	
H310 - Fatal in contact with skin	exposure	
H311 - Toxic in contact with skin	H400 - Very toxic to aquatic life	
H312 - Harmful in contact with skin	 H410 - Very toxic to aquatic life with long lasting effects 	
 H314 - Causes severe skin burns and eye damage 	 H411 - Toxic to aquatic life with long lasting effects 	
H315 - Causes skin irritation	 H412 - Harmful to aquatic life with long lasting effects 	
 H317 - May cause an allergic skin reaction 	 H413 - May cause long lasting harmful effects to aquatic life 	
H318 - Causes serious eye damage	H360Df - May damage the unborn child. Suspected of damaging fertility	
H319 - Causes serious eye irritation	 H360D - May damage the unborn child 	
H330 - Fatal if inhaled	 H360FD - May damage fertility. May damage the unborn child 	
H331 - Toxic if inhaled	H360F - May damage fertility	
H332 - Harmful if inhaled	 H361d - Suspected of damaging the unborn child 	
• H334 - May cause allergy or asthma symptoms or breathing difficulties	 H361fd - Suspected of damaging fertility. Suspected of damaging the 	
if inhaled	unborn child	
H335 - May cause respiratory irritation	 H361f - Suspected of damaging fertility 	
H336 - May cause drowsiness or dizziness	• EUH066 - Repeated exposure may cause skin dryness or cracking	
H340 - May cause genetic defects	• EUH210 - Safety data sheet available on request	
	• EUH208 - May produce an allergic reaction	
	· · · · · · · · · · · · · · · · · · ·	

Exposure scenario

No information available

Revision Date:

08-16-2016

Revision Note

(M)SDS sections updated, 15.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.