



# SAFETY DATA SHEET

Gulf DCT Fluid

04129/2

Issuing Date 05-06-2020

Revision Date 05-06-2020

Version 1

## SECTION 1: IDENTIFICATION: PRODUCT IDENTIFIER AND CHEMICAL IDENTITY

### Product identifier

**Product Name** Gulf DCT Fluid  
**Product Code(s)** 04129/2

### Other means of identification

**UN Number** Not Applicable

### Recommended use of the chemical and restrictions on use

**Recommended Use** Automatic transmission fluids

**Uses advised against** Any other purpose.

### Suppliers name, address and phone number

Gulf Oil Supply Company Limited  
B2 Industry Street, Qormi, QRM 3000, Malta  
Tel: +44 207 321 6219  
E-mail: products@gulfoilltd.com, sds@gulfoilltd.com

(+) 44 808 189 0979 (Code 334276)

(+) 1 760 476 3961 (Code 334276)

(+) 32 (0) 3241 33 55

### Emergency telephone number

**Poison Information Center telephone number** (AU) 13 11 26, (NZ) 0800 764 766

## SECTION 2: HAZARDS IDENTIFICATION

### GHS Classification

Not a dangerous substance or mixture according to the Globally Harmonized System (GHS)

### Label elements

**Signal word**  
None

**Hazard statements**  
None

**Precautionary Statements**  
None

### Other hazards

Causes mild skin irritation  
May cause sensitization of susceptible persons by skin contact

### SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

This product is a mixture. Health hazard information is based on its ingredients

Chemical name	CAS No	Weight-%
Highly refined, low viscosity mineral oils/hydrocarbons (Viscosity >7 - <20.5 cSt @40°C)	-	60% - 100%
Reaction products of fatty acids, C14-C18 (branched and linear) and C18 (unsaturated) with tetraethylenepentamine (linear, branched, cyclic)	68784-17-8	1% - 2.5%
2-ethylhexyl methacrylate	688-84-6	0% - 1%
C14-18 alpha-olefin epoxide, reaction products with boric acid	NOT AVAILABLE	0% - 1%

Product containing mineral oil with less than 3% DMSO extract as measured by IP 346. The highly refined base oil may be described by one or more of the following generic CAS identifiers: 64742-54-7, 64742-65-0, 64742-52-5, 64742-53-6, 64742-62-7, 64742-57-0, 64742-01-4, 64741-88-4, 64742-96-4, 64741-97-5, 64742-55-8, 64742-56-9, 64741-89-5, 8042-47-5. See Section 15 for additional information on base oils.

### SECTION 4: FIRST AID MEASURES

#### Description of first aid measures

<b>General advice</b>	May produce an allergic reaction. When symptoms persist or in all cases of doubt seek medical advice.
<b>Inhalation</b>	Move to fresh air.
<b>Skin contact</b>	Wash off immediately with plenty of water for at least 15 minutes. Remove and wash contaminated clothing before re-use. May cause an allergic skin reaction. If symptoms persist, call a physician.
<b>Eye contact</b>	Rinse thoroughly with plenty of water, also under the eyelids. Keep eye wide open while rinsing.
<b>Ingestion</b>	Clean mouth with water. Drink plenty of water. Do not induce vomiting without medical advice.
<b>Protection of First-aiders</b>	Use personal protective equipment. Avoid contact with skin, eyes and clothing.

#### Most important symptoms and effects, both acute and delayed

**Main Symptoms** May cause allergic skin reaction, Rashes, Itching

#### Indication of any immediate medical attention and special treatment needed

**Notes to physician** May cause sensitization of susceptible persons. Treat symptomatically.

### SECTION 5: FIRE FIGHTING MEASURES

#### Extinguishing media

##### **Suitable Extinguishing Media**

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.: Use CO2, dry chemical, or foam, Water spray or fog, Cool containers with flooding quantities of water until well after fire is out

**Extinguishing media which shall not be used for safety reasons**

Do not use a solid water stream as it may scatter and spread fire

**Specific hazards arising from the chemical**

Thermal decomposition can lead to release of irritating gases and vapors. In the event of fire and/or explosion do not breathe fumes. This material creates a fire hazard because it floats on water.

**Hazardous decomposition products**

Carbon monoxide (CO), carbon dioxide (CO<sub>2</sub>)

**Advice for firefighters****Special protective equipment for fire-fighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear

**SECTION 6: ACCIDENTAL RELEASE MEASURES****Personal precautions, protective equipment and emergency procedures**

Remove all sources of ignition. Ensure adequate ventilation. Use personal protective equipment. Avoid contact with skin, eyes and clothing. Wash thoroughly after handling. Take precautionary measures against static discharges.

**Advice for non-emergency personnel**

Material can create slippery conditions.

**Advice for emergency responders** For personal protection see section 8.

**Environmental precautions**

Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.

**Methods and material for containment and cleaning up**

Dike to collect large liquid spills

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Take up mechanically and collect in suitable container for disposal.

**Reference to other sections**

See also section 8/12/13

**SECTION 7: HANDLING AND STORAGE****Precautions for safe handling**

Ensure adequate ventilation. Do not eat, drink or smoke when using this product. Handle in accordance with good industrial hygiene and safety practice. Wash thoroughly after handling. Wear personal protective equipment. Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Keep away from open flames, hot surfaces and sources of ignition.

**Conditions for safe storage, including any incompatibilities****Technical measures/Storage conditions**

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from open flames, hot surfaces and sources of ignition.

**Incompatible materials**

Oxidizing agent

**Recommended Use** Automatic transmission fluids

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

### Exposure Limits

Chemical name	Australia	New Zealand	New Zealand - Biological Exposure Indices (BEI)
Highly refined, low viscosity mineral oils/hydrocarbons (Viscosity >7 - <20.5 cSt @40°C)	TWA: 5 mg/m <sup>3</sup>	TWA: 5 mg/m <sup>3</sup> STEL: 10 mg/m <sup>3</sup>	

*Australia - Workplace Exposure Standards for Airborne Contaminants.  
New Zealand - Workplace Exposure Standards and Biological Exposure Indices.*

### Appropriate engineering controls

**Engineering controls** Ensure adequate ventilation, especially in confined areas.

### Individual protection measures, such as personal protective equipment

<b>Eye/face protection</b>	Safety glasses with side-shields.
<b>Skin and body protection</b>	Long sleeved clothing.
<b>Hand Protection</b>	Protective gloves. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.
<b>Respiratory protection</b>	No special protective equipment required. In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit.

**Hygiene measures** Regular cleaning of equipment, work area and clothing is recommended.

**Environmental Exposure Controls** No special environmental precautions required.  
**Thermal hazards** None under normal use conditions

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

<b>Physical state</b>	Liquid	<b>Appearance</b>	clear amber
<b>Odor</b>	Hydrocarbon-like	<b>Odor threshold</b>	Not Determined

<u>Property</u>	<u>Values</u>	<u>Remarks</u>
<b>pH</b>	Not Determined	
<b>Melting point / freezing point</b>	Not determined	
<b>Boiling point / boiling range</b>	Not determined	
<b>Flash point</b>	204 °C / 399 °F	ASTM D 92
<b>Evaporation rate</b>	negligible	
<b>Flammability (solid, gas)</b>	Not Determined	
<b>Flammability Limit in Air</b>		
<b>Upper flammability or explosive limits</b>	Not determined	

<b>Lower flammability or explosive limits</b>	Not determined	
<b>Vapor pressure</b>	Not determined	
<b>Vapor density</b>	Not determined	
<b>Relative density</b>	0.8508 @ 15 °C	
<b>Solubility(ies)</b>	Insoluble in water	
<b>Partition coefficient</b>	not determined	
<b>Autoignition temperature</b>	Not Determined	
<b>Decomposition temperature</b>	No data available	
<b>Kinematic viscosity</b>	35 cSt @ 40 °C	ASTM D 445
<b>Explosive properties</b>	Not applicable	
<b>Oxidizing Properties</b>	Not applicable	

**Other Information**

<b>Viscosity, kinematic (100°C)</b>	7.3 cSt @ 100°C	ASTM D 445
<b>Pour Point</b>	-48 °C / -54 °F	ASTM D 97
<b>VOC Content (ASTM E-1868-10)</b>	Not Determined	
<b>VOC content</b>	Not Determined	

**SECTION 10: STABILITY AND REACTIVITY****Reactivity**

None under normal use conditions

**Chemical stability**

Stable under normal conditions

**Possibility of hazardous reactions**

None under normal use conditions

**Conditions to avoid**

Keep away from open flames, hot surfaces and sources of ignition, Extremes of temperature and direct sunlight

**Incompatible materials**

Oxidizing agent

**Hazardous decomposition products**

Incomplete combustion and thermolysis produces potentially toxic gases such as carbon monoxide and carbon dioxide.

**SECTION 11: TOXICOLOGICAL INFORMATION****Information on the likely routes of exposure****Product Information - Principle Routes of Exposure**

<b>Inhalation</b>	None known
<b>Eye contact</b>	None known
<b>Skin contact</b>	Based on available data, the classification criteria are not met. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. Mild skin irritation

Ingestion None known

#### Numerical measures of toxicity - Product Information

ATEmix (oral) >2000 mg/kg  
ATEmix (dermal) >2000 mg/kg mg/l

#### Acute toxicity - Product Information

Product does not present an acute toxicity hazard based on known or supplied information.

#### Acute toxicity - Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Highly refined, low viscosity mineral oils/hydrocarbons (Viscosity >7 - <20.5 cSt @40°C)	>2000 mg/kg	>2000 mg/kg	>5 mg/L

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Skin corrosion/irritation** Based on available data, the classification criteria are not met. Mild skin irritant.

**Serious eye damage/eye irritation** Based on available data, the classification criteria are not met.

#### **Sensitization**

##### **Respiratory Sensitization**

Based on available data, the classification criteria are not met.

##### **Skin sensitization**

Based on available data, the classification criteria are not met. Repeated contact may cause allergic reactions in very susceptible persons.

**Germ cell mutagenicity** Based on available data, the classification criteria are not met.

**Carcinogenicity** Based on available data, the classification criteria are not met.

**Reproductive toxicity** Based on available data, the classification criteria are not met.

**Aspiration hazard** Based on available data, the classification criteria are not met.

**Exposure levels** See section 8 for more information

**Interactive effects** None known

## SECTION 12: ECOLOGICAL INFORMATION

#### Toxicity

No special environmental measures are necessary

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Highly refined, low viscosity mineral oils/hydrocarbons (Viscosity >7 - <20.5 cSt @40°C)	>100: 72 h mg/L	>100: 96 h mg/L		>100: 48 h mg/L
Reaction products of fatty acids, C14-C18 (branched and linear) and C18 (unsaturated) with tetraethylenepentamine	94: 72 h Selenastrum capricornutum mg/L EC50	>1000: 96 h Pimephales promelas mg/L LC50 semi-static		>1000: 48 h Daphnia magna mg/L EC50

(linear, branched, cyclic)			
2-ethylhexyl methacrylate		2.78: 96 h Red Killifish mg/L LC50	0.105: 48 h Daphnia magna mg/L EC50
C14-18 alpha-olefin epoxide, reaction products with boric acid	>100: 72 h Selenastrum capricornutum mg/L EC50	>100: 96 h Oncorhynchus mykiss mg/L LC50	>100: 48 h Daphnia magna mg/L EC50

**Persistence and degradability**

The product is not readily biodegradable, but it can be degraded by micro-organisms, it is regarded as being inherently biodegradable.

**Bioaccumulative potential**

No information available

**Mobility in soil**

No information available

**Other adverse effects**

None known

## SECTION 13: DISPOSAL CONSIDERATIONS

**Safe handling and disposal methods**

Dispose of in accordance with local regulations

**Disposal of any contaminated packaging**

Empty containers should be taken to an approved waste handling site for recycling or disposal. Observe all label precautions until container is cleaned, reconditioned or destroyed.

**Environmental regulations**

No information available

## SECTION 14: TRANSPORT INFORMATION

**ADG** Not regulated

**IMDG** Not regulated

**IATA** Not regulated

## SECTION 15: REGULATORY INFORMATION

**Safety, health and environmental regulations/legislation specific for the substance or mixture****National regulations****Australia**

Model Work Health and Safety Regulations (2016).  
Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice (2011).

**Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)**

No poisons schedule number allocated

### New Zealand

Hazardous Substances Regulation 2001.

#### **New Zealand**

**HSNO Approval Number:**

**HSNO Hazard Classification:**

Lubricants (Low Hazard) Group Standard 2006

HSR002605

6.3B

### International Regulations

#### **Ozone-depleting substances (ODS)**

Not applicable

#### **The Stockholm Convention on Persistent Organic Pollutants**

Not applicable

#### **The Rotterdam Convention**

Not applicable

### International Inventories

#### **TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

All ingredients are on the inventory or exempt from listing

#### **DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List

All ingredients are on the inventory or exempt from listing

#### **AICS** - Australian Inventory of Chemical Substances

All ingredients are on the inventory or exempt from listing

#### **PICCS** - Philippines Inventory of Chemicals and Chemical Substances

All ingredients are on the inventory or exempt from listing

#### **KECL** - Korean Existing and Evaluated Chemical Substances

All ingredients are on the inventory or exempt from listing

#### **IECSC** - China Inventory of Existing Chemical Substances

All ingredients are on the inventory or exempt from listing

#### **ENCS** - Japan Existing and New Chemical Substances

All ingredients are on the inventory or exempt from listing

#### **TCSI** - Taiwan National Existing Chemical Inventory

Contact supplier for inventory compliance status

#### **NZIoC** - New Zealand Inventory of Chemicals

All ingredients are on the inventory or exempt from listing

### Other Information

---



The highly refined, low viscosity mineral oils/hydrocarbons (Viscosity >7 - <20.5 cSt @40°C) contains one or more substance with the following CAS/EC numbers:

Chemical name	CAS No	EC No
Distillates (petroleum), hydrotreated heavy paraffinic	63742-54-7	265-157-1
Distillates (petroleum), heavy hydrocracked	64741-76-0	265-077-7
Distillates (petroleum), solvent-refined heavy paraffinic	64741-88-4	265-090-8
Distillates (petroleum), solvent-refined light paraffinic	64741-89-5	265-091-3
Residual oils (petroleum), solvent deasphalted	64741-95-3	265-096-0
Distillates (petroleum), solvent-refined heavy naphthenic	64741-96-4	265-097-6
Distillates (petroleum), solvent-refined light naphthenic	64741-97-5	265-098-1
Residual oils (petroleum), solvent-refined	64742-01-4	265-101-6
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	265-155-0
Distillates (petroleum), hydrotreated light naphthenic	64742-53-6	265-156-6
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	265-157-1
Distillates (petroleum), hydrotreated light paraffinic	64742-55-8	265-158-7
Distillates (petroleum), solvent-dewaxed light paraffinic	64742-56-9	265-159-2
Residual oils (petroleum), hydrotreated	64742-57-0	265-160-8
Lubricating oils (petroleum), hydrotreated spent	64742-58-1	265-161-3
Residual oils (petroleum), solvent-dewaxed	64742-62-7	265-166-0
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	265-169-7
Paraffin oils (petroleum), catalytic dewaxed light	64742-71-8	265-176-5
Dec-1-ene, homopolymer, hydrogenated	68037-01-4	500-183-1
Lubricating oils (petroleum), C>25, hydrotreated bright stock-based	72623-83-7	276-735-8
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, high-viscosity	72623-85-9	276-736-3
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	72623-86-0	276-737-9
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	72623-87-1	276-738-4
Lubricating oils	74869-22-0	278-012-2

## SECTION 16: OTHER INFORMATION

**Issuing Date** 05-06-2020  
**Revision Date** 05-06-2020  
**Revision Note** Initial Release

### Key or legend to abbreviations and acronyms used in the safety data sheet

TWA Time weighted average STEL Short term exposure limit  
 Ceiling Maximum limit value: (s) - Skin Skin designation  
 + Sensitizers C Carcinogen  
 STOT SE - Specific target organ systemic toxicity (Single exposure)  
 STOT RE - Specific target organ systemic toxicity (repeated exposure)  
 VOC - Volatile organic compounds

### Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of Safety Data Sheet**