



SAFETY DATA SHEET

Gulf ATF DX III

04109/1

Issuing Date 03-26-2017

Revision Date 03-26-2017

Version 1

SECTION 1: IDENTIFICATION: PRODUCT IDENTIFIER AND CHEMICAL IDENTITY

Product identifier

Product Name Gulf ATF DX III
Product Code(s) 04109/1

Other means of identification

UN Number Not Applicable

Recommended use of the chemical and restrictions on use

Recommended Use Automatic transmission fluids

Uses advised against Any other purpose.

Suppliers name, address and phone number

Gulf Oil Supply Company Limited
B2 Industry Street, Qormi, QRM 3000, Malta
+44 207 321 6219
products@gulfoilltd.com sds@gulfoilltd.com

Emergency telephone number

Europe (+) 44 808 189 0979 Code 334276
(+) 1 760 476 3961 Code 334276
(+) 32 (0) 3241 33 55

Poison Information Center telephone number (AU) 13 11 26, (NZ) 0800 764 766

SECTION 2: HAZARDS IDENTIFICATION

GHS Classification

Not a dangerous substance or mixture according to the Globally Harmonized System (GHS)

Label elements

Signal word
None

Hazard statements
None

Precautionary Statements

None

Other hazards

Causes mild skin irritation

May cause sensitization of susceptible persons by skin contact

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

This product is a mixture. Health hazard information is based on its ingredients

Chemical name	CAS No	Weight-%
Highly refined, low viscosity mineral oils/hydrocarbons (Viscosity >7 - <20.5 cSt @40°C)	-	60% - 100%
Highly refined base oil (Viscosity >20.5 cSt @40°C)	-	2.5% - 10%

Additional information

Product containing mineral oil with less than 3% DMSO extract as measured by IP 346

See Section 15 for additional information on base oils.

The remaining composition is a mixture of non-classified ingredients or additives below the threshold for disclosure

SECTION 4: FIRST AID MEASURES**Description of first-aid measures****General advice**

May produce an allergic reaction. When symptoms persist or in all cases of doubt seek medical advice.

Inhalation

Move to fresh air.

Skin contact

Wash off immediately with plenty of water for at least 15 minutes. Remove and wash contaminated clothing before re-use. May cause an allergic skin reaction. If symptoms persist, call a physician.

Eye contact

Rinse thoroughly with plenty of water, also under the eyelids. Keep eye wide open while rinsing.

Ingestion

Clean mouth with water. Drink plenty of water. Do not induce vomiting without medical advice.

Protection of First-aiders

Use personal protective equipment. Avoid contact with skin, eyes and clothing.

Most important symptoms and effects, both acute and delayed**Main Symptoms**

May cause allergic skin reaction

Indication of immediate medical attention and special treatment needed**Notes to physician**

May cause sensitization of susceptible persons. Treat symptomatically.

SECTION 5: FIRE FIGHTING MEASURES**Extinguishing media****Suitable Extinguishing Media**

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.: Use CO2, dry chemical, or foam, Water spray or fog, Cool containers / tanks with water spray

Extinguishing media which shall not be used for safety reasons

Do not use a solid water stream as it may scatter and spread fire

Specific hazards arising from the chemical

Thermal decomposition can lead to release of irritating gases and vapors. Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke). In the event of fire and/or explosion do not breathe fumes. This material creates a fire hazard because it floats on water.

Hazardous decomposition products

Incomplete combustion and thermolysis produces potentially toxic gases such as carbon monoxide and carbon dioxide

Advice for firefighters**Special protective equipment for fire-fighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear

SECTION 6: ACCIDENTAL RELEASE MEASURES**Personal precautions, protective equipment and emergency procedures**

Remove all sources of ignition. Ensure adequate ventilation. Use personal protective equipment. Avoid contact with skin, eyes and clothing.

Advice for non-emergency personnel Material can create slippery conditions.

Advice for emergency responders For personal protection see section 8.

Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.

Methods and materials for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Dike to collect large liquid spills.

Reference to other sections

See Section 8/12/13 for additional information

SECTION 7: HANDLING AND STORAGE**Precautions for safe handling**

Ensure adequate ventilation. Do not eat, drink or smoke when using this product. Handle in accordance with good industrial hygiene and safety practice. Wear personal protective equipment. Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use.

Conditions for safe storage, including any incompatibilities**Technical measures/Storage conditions**

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from open flames, hot surfaces and sources of ignition.

Incompatible materials

Oxidizing agent

Recommended Use

Automatic transmission fluids

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters**Exposure Limits**

Chemical name	Australia	New Zealand	New Zealand - Biological Exposure Indices (BEI)
Highly refined, low viscosity mineral oils/hydrocarbons (Viscosity >7 - <20.5 cSt @40°C)		TWA: 5 mg/m ³ STEL: 10 mg/m ³	
Highly refined base oil (Viscosity >20.5 cSt @40°C)		TWA: 5 mg/m ³ STEL: 10 mg/m ³	

Australia - Workplace Exposure Standards for Airborne Contaminants. New Zealand - Workplace Exposure Standards and Biological Exposure Indices.

Appropriate engineering controls

Engineering controls Ensure adequate ventilation, especially in confined areas.

Individual protection measures, such as personal protective equipment

Eye/face protection Safety glasses with side-shields.
Skin and body protection Long sleeved clothing.
Hand Protection Protective gloves. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.
Respiratory protection No special protective equipment required. In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit.

Hygiene measures Do not eat, drink or smoke when using this product. Handle in accordance with good industrial hygiene and safety practice.

Environmental Exposure Controls No special environmental precautions required.
Thermal hazards None under normal use conditions

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state	liquid	Appearance	clear amber
Odor	Hydrocarbon-like	Odor threshold	Not Determined

<u>Property</u>	<u>Values</u>	<u>Remarks</u>
pH	Not Determined	
Melting point / freezing point	Not Determined	
Boiling point / boiling range	Not Determined	
Flash point	188 °C / 370 °F	ASTM D 92
Evaporation rate	Not Determined	
Flammability (solid, gas)	Not Determined	
Flammability Limit in Air		
Upper flammability limit:	Not Determined	
Lower flammability limit:	Not Determined	
Vapor pressure	Not Determined	
Vapor density	Not Determined	

Relative density	0.8296	@15°C
Solubility(ies)	Insoluble in water	
Partition coefficient	Not Determined	
Autoignition temperature	Not Determined	
Decomposition temperature	Not Determined	
Kinematic viscosity	34.76 cSt @ 40 °C	ASTM D 445
Explosive properties	Not applicable	
Oxidizing Properties	Not applicable	

Other Information

Viscosity, kinematic (100°C)	7.9 cSt @ 100°C	ASTM D 445
Pour Point	-39 °C / -38 °F	ASTM D 97
VOC Content (ASTM E-1868-10)	Not Determined	
VOC content	Not Determined	

SECTION 10: STABILITY AND REACTIVITY**Reactivity**

None under normal use conditions

Chemical stability

Stable under normal conditions

Possibility of hazardous reactions

None under normal use conditions

Conditions to avoid

Keep away from open flames, hot surfaces and sources of ignition, Extremes of temperature and direct sunlight

Incompatible materials

Oxidizing agent

Hazardous decomposition products

Incomplete combustion and thermolysis produces potentially toxic gases such as carbon monoxide and carbon dioxide.

SECTION 11: TOXICOLOGICAL INFORMATION**Information on the likely routes of exposure****Product Information - Principle Routes of Exposure**

Inhalation	None known
Eye contact	None known
Skin contact	Mild skin irritation; Repeated or prolonged skin contact may cause allergic reactions with susceptible persons
Ingestion	None known

Numerical measures of toxicity - Product Information

ATEmix (oral)	>2000 mg/kg
---------------	-------------

ATEmix (dermal) >2000 mg/kg

Acute toxicity - Product Information

Product does not present an acute toxicity hazard based on known or supplied information.

Acute toxicity - Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Highly refined, low viscosity mineral oils/hydrocarbons (Viscosity >7 - <20.5 cSt @40°C)	>2000 mg/kg	>2000 mg/kg	
Highly refined base oil (Viscosity >20.5 cSt @40°C)	>2000 mg/kg	>2000 mg/kg	

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation	Mild skin irritant.
Serious eye damage/eye irritation	Based on available data, the classification criteria are not met.
Sensitization	
Respiratory Sensitization	Based on available data, the classification criteria are not met.
Skin sensitization	Repeated contact may cause allergic reactions in very susceptible persons.
Germ cell mutagenicity	Based on available data, the classification criteria are not met.
Carcinogenicity	Based on available data, the classification criteria are not met.
Reproductive toxicity	Based on available data, the classification criteria are not met.
Specific target organ systemic toxicity (single exposure)	Based on available data, the classification criteria are not met
Specific target organ systemic toxicity (repeated exposure)	Based on available data, the classification criteria are not met
Aspiration hazard	Based on available data, the classification criteria are not met.
Exposure levels	See section 8 for more information
Interactive effects	None known

SECTION 12: ECOLOGICAL INFORMATION

Toxicity

No special environmental measures are necessary

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Highly refined, low viscosity mineral oils/hydrocarbons (Viscosity >7 - <20.5 cSt @40°C)	>100: 72 h mg/L	>100: 96 h mg/L		>100: 48 h mg/L
Highly refined base oil (Viscosity >20.5 cSt @40°C)	>100: 72 h mg/L	>100: 96 h mg/L		>100: 48 h mg/L

Persistence and degradability

The product is not readily biodegradable, but it can be degraded by micro-organisms, it is regarded as being inherently biodegradable.

Bioaccumulative potential

No information available

Mobility

The product is insoluble and floats on water

Other adverse effects

None known

SECTION 13: DISPOSAL CONSIDERATIONS**Safe handling and disposal methods**

Dispose of in accordance with local regulations

Disposal of any contaminated packaging

Empty containers should be taken to an approved waste handling site for recycling or disposal. Observe all label precautions until container is cleaned, reconditioned or destroyed.

Environmental regulations

No information available

SECTION 14: TRANSPORT INFORMATION

ADG Not regulated

IMDG Not regulated

IATA Not regulated

SECTION 15: REGULATORY INFORMATION**Safety, health and environmental regulations/legislation specific for the substance or mixture****National regulations****Australia**

Model Work Health and Safety Regulations (2016).
Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice (2011).

Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)

No poisons schedule number allocated

New Zealand

Hazardous Substances Regulation 2001.

New Zealand

Lubricants, Lubricant Additives, Coolants and Anti-freeze Agents
(Subsidiary Hazard) Group Standard 2006
HSR002606
6.3B

HSNO Approval Number:

HSNO Hazard Classification:

International Regulations

Ozone-depleting substances (ODS)

Not applicable

Persistent Organic Pollutants

Not applicable

Chemicals Subject to Prior Informed Consent (PIC)

Not applicable

International Inventories

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

All ingredients are on the inventory or exempt from listing

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

All ingredients are on the inventory or exempt from listing

AICS - Australian Inventory of Chemical Substances

All ingredients are on the inventory or exempt from listing

PICCS - Philippines Inventory of Chemicals and Chemical Substances

All ingredients are on the inventory or exempt from listing

KECL - Korean Existing and Evaluated Chemical Substances

All ingredients are on the inventory or exempt from listing

IECSC - China Inventory of Existing Chemical Substances

All ingredients are on the inventory or exempt from listing

ENCS - Japan Existing and New Chemical Substances

All ingredients are on the inventory or exempt from listing

TCSI - Taiwan National Existing Chemical Inventory

Contact supplier for inventory compliance status

NZIoC - New Zealand Inventory of Chemicals

All ingredients are on the inventory or exempt from listing

Other Information

The highly refined base oil (Viscosity >20.5 cSt @40°C) contains one or more substance with the following CAS/EC numbers:

Chemical name	CAS No	EC-No
Distillates (petroleum), solvent-refined heavy paraffinic	64741-88-4	265-090-8
Distillates (petroleum), solvent-refined light paraffinic	64741-89-5	265-091-3

Residual oils (petroleum), solvent deasphalted	64741-95-3	265-096-0
Distillates (petroleum), solvent-refined heavy naphthenic	64741-96-4	265-097-6
Distillates (petroleum), solvent-refined light naphthenic	64741-97-5	265-098-1
Residual oils (petroleum), solvent-refined	64742-01-4	265-101-6
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	265-155-0
Distillates (petroleum), hydrotreated light naphthenic	64742-53-6	265-156-6
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	265-157-1
Distillates (petroleum), hydrotreated light paraffinic	64742-55-8	265-158-7
Distillates (petroleum), solvent-dewaxed light paraffinic	64742-56-9	265-159-2
Residual oils (petroleum), hydrotreated	64742-57-0	265-160-8
Lubricating oils (petroleum), hydrotreated spent	64742-58-1	265-161-3
Residual oils (petroleum), solvent-dewaxed	64742-62-7	265-166-0
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	265-169-7
Paraffin oils (petroleum), catalytic dewaxed heavy	64742-70-7	265-174-4
Paraffin oils (petroleum), catalytic dewaxed light	64742-71-8	265-176-5
Lubricating oils (petroleum), C>25, hydrotreated bright stock-based	72623-83-7	276-735-8
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, high-viscosity	72623-85-9	276-736-3
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	72623-86-0	276-737-9
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	72623-87-1	276-738-4
Lubricating oils	74869-22-0	278-012-2
White mineral oil (petroleum)	8042-47-5	232-455-8

The highly refined, low viscosity mineral oils/hydrocarbons (Viscosity >7 - <20.5 cSt @40°C) contains one or more substance with the following CAS/EC numbers:

Chemical name	CAS No	EC-No
Distillates (petroleum), hydrotreated heavy paraffinic	63742-54-7	265-157-1
Distillates (petroleum), solvent-refined heavy paraffinic	64741-88-4	265-090-8
Distillates (petroleum), solvent-refined light paraffinic	64741-89-5	265-091-3
Residual oils (petroleum), solvent deasphalted	64741-95-3	265-096-0
Distillates (petroleum), solvent-refined heavy naphthenic	64741-96-4	265-097-6
Distillates (petroleum), solvent-refined light naphthenic	64741-97-5	265-098-1
Residual oils (petroleum), solvent-refined	64742-01-4	265-101-6
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	265-155-0
Distillates (petroleum), hydrotreated light naphthenic	64742-53-6	265-156-6
Distillates (petroleum), hydrotreated light paraffinic	64742-55-8	265-158-7
Distillates (petroleum), solvent-dewaxed light paraffinic	64742-56-9	265-159-2
Residual oils (petroleum), hydrotreated	64742-57-0	265-160-8
Lubricating oils (petroleum), hydrotreated spent	64742-58-1	265-161-3
Residual oils (petroleum), solvent-dewaxed	64742-62-7	265-166-0
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	265-169-7
Paraffin oils (petroleum), catalytic dewaxed light	64742-71-8	265-176-5
Dec-1-ene, homopolymer, hydrogenated	68037-01-4	500-183-1
Lubricating oils (petroleum), C>25, hydrotreated bright stock-based	72623-83-7	276-735-8
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, high-viscosity	72623-85-9	276-736-3
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	72623-86-0	276-737-9
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	72623-87-1	276-738-4
Lubricating oils	74869-22-0	278-012-2

SECTION 16: OTHER INFORMATION

Issuing Date

03-26-2017

Revision Date 03-26-2017
Revision Note Initial Release

Key or legend to abbreviations and acronyms used in the safety data sheet

TWA	Time weighted average	STEL	Short term exposure limit
Ceiling	Maximum limit value:	(s) - Skin	Skin designation
+	Sensitizers	C	Carcinogen

STOT SE - Specific target organ systemic toxicity (Single exposure)
STOT RE - Specific target organ systemic toxicity (repeated exposure)
VOC - Volatile organic compounds

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet