



Gulf ATF DX III H

Extra high performance Automatic Transmission Fluid

Product Description

Gulf ATF DX III H is an extra high performance automatic transmission fluid for all General Motors and Ford automatic transmissions requiring DEXRON®-III (including the new DEXRON® III H specification) or MERCON® quality fluids respectively. The modern additive technology and specially selected base oils used in this oil provide superior thermo-oxidative stability, corrosion & rust protection, foam control, seal compatibility, friction durability and low temperature fluidity. It is designed to exceed the performance requirements of General Motors DEXRON® III H and Ford MERCON® specifications.

Features & Benefits

- Superior thermo-oxidative stability, wear protection and resistance to chemical deterioration can provide longer fluid and component life
- Controlled frictional properties lead to smooth shift performance, efficient transmission of power and prevent shudder
- Extremely high Viscosity index ensures adequate lubrication in both high operating & low starting temperatures
- Provides excellent protection against rust and corrosion
- Effective foam control leads to smooth & lasting shift feel and reduces fluid loss
- Improved low temperature fluidity leads to easy pumping in the hydraulic circuits
- Better seal compatibility ensures longer seal life and reduces possibility of oil leakage

Applications

- Recommended for all vehicles of Ford requiring MERCON® quality fluids and General Motors requiring DEXRON®-III H quality fluids.
- Being back serviceable, also recommended for automatic transmissions requiring General Motors DEXRON® III , DEXRON® II E or DEXRON® II D fluids and also for imported cars like Audi, Honda, Mazda, Nissan, Opel, Renault, Toyota and Volkswagen where such fluids are specified

Specifications, Approvals & Typical Properties

Meets the following Specifications		
General Motors DEXRON® III H		X
Ford MERCON®		X
Has the following Approvals		
Volvo Transmission Oil 97341 approval		X
ZF TE-ML 04D, 14A (ZF Approval Number: ZF000078)		X
MAN 339 Typ L1 and MAN 339 Typ Z1		X
Typical Properties		
Test Parameters	ASTM Method	Typical Values
Viscosity @ 100 °C, cSt	D 445	7.4
Viscosity Index	D 2270	178
Flash Point, °C	D 92	216
Pour Point, °C	D 97	-48
Brookfield Viscosity @ -40 °C, cP	D 2983	18456
Density @ 15°C, Kg/l	D 1298	0.857

DEXRON® is a registered trademark of General Motors Corporation
MERCON® is a registered trademark of Ford Motor Company

April 2016

Properties mentioned above are typical only and minor variations, which do not affect the product performances, are to be expected in normal manufacturing. The above information is based on past history of the grade only and must not be construed as a guarantee of performance. Follow equipment manufacturer's recommendations for performance level and viscosity grade. The Material Safety Data Sheet for this product is available from your nearest Gulf Distributor.

Gulf Oil International

The information contained herein is believed to be correct at time of publication. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of the products. Gulf Oil International reserves the right to modify and change its products and specifications without prior notice.

www.gulfoilltd.com