

# SAFETY DATA SHEET

Gulf Superfleet XLE, 10W-40

02111/10W-40/5

**Issuing Date** 08-02-2022

Revision Date 08-02-2022

Version 1

# SECTION 1: IDENTIFICATION: PRODUCT IDENTIFIER AND CHEMICAL IDENTITY

Product identifier

Product NameGulf Superfleet XLE, 10W-40Product Code(s)02111/10W-40/5

Other means of identification

UN number or ID number Not Applicable

Recommended use of the chemical and restrictions on use

Recommended use Engine oil

Uses advised against Any other purpose.

## Suppliers name, address and phone number

AR Oil Distribution Pty Ltd official licensee of Gulf Oil International for Australia 12 Greycliffe Ave Pennant Hills NSW 2120 Australia Tel: +61 (0) 411404594

AB Equipment Ltd official licensee of Gulf Oil International for New Zealand 12 Pukekiwiriki Place Highbrook Drive Auckland Tel: (+) 64 0800 30 30 90

products@gulfoilltd.com, sds@gulfoilltd.com

## Emergency Telephone Number

AU: (+) 61 1 800 686 951 (Code 334276) NZ: (+) 64 800 451719 (Code 334276)

Poison Information Center telephone (AU) 13 11 26, (NZ) 0800 764 766 number

# **SECTION 2: HAZARDS IDENTIFICATION**

## GHS Classification

Not a dangerous substance or mixture according to the Globally Harmonized System (GHS)

## Label elements

Signal word None

Hazard statements None

Precautionary Statements None

Other hazards which do not result in classification Repeated contact may cause allergic reactions in very susceptible persons

# **SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

This product is a mixture. Health hazard information is based on its ingredients

Chemical name	CAS No.	Weight-%
Highly refined base oil (Viscosity >20.5 cSt @40°C)	-	60% - 100%
Highly refined, low viscosity mineral oils/hydrocarbons (Viscosity >7 - <20.5 cSt @40°C)	-	25% - 60%
Phosphorodithioic acid, mixed O,O-bis(sec-Bu and 1,3-dimethylbutyl) esters, zinc salts	68784-31-6	1% - 2.5%

Product containing mineral oil with less than 3% DMSO extract as measured by IP 346. The highly refined base oil may be described by one or more of the following generic CAS identifiers: 64742-54-7, 64742-65-0, 64742-52-5, 64742-53-6, 64742-62-7, 64742-57-0, 64742-01-4, 64741-88-4, 64741-96-4, 64741-97-5, 64742-55-8, 64742-56-9, 64741-89-5, 8042-47-5. See Section 15 for additional information on base oils.

The remaining composition is a mixture of non-classified ingredients or additives below the threshold for disclosure

# **SECTION 4: FIRST AID MEASURES**

#### Description of first aid measures

General advice	May produce an allergic reaction. If symptoms persist, call a physician.
Inhalation	Remove to fresh air.
Skin contact	Wash off immediately with plenty of water for at least 15 minutes. Remove and wash contaminated clothing before re-use. May cause an allergic skin reaction. If symptoms persist, call a physician.
Eye contact	Rinse thoroughly with plenty of water, also under the eyelids. Keep eye wide open while rinsing.
Ingestion	Clean mouth with water. Drink plenty of water. Do not induce vomiting without medical advice.
Protection of First-aiders	Use personal protective equipment. Avoid contact with skin, eyes and clothing.
Most important symptoms and effect	cts, both acute and delayed
Main Symptoms	Prolonged contact may cause redness and irritation, Rashes, Itching
Indication of any immediate medical attention and special treatment needed	

#### Notes to physician

May cause sensitization of susceptible persons. Treat symptomatically.

# **SECTION 5: FIRE FIGHTING MEASURES**

#### Extinguishing media

#### Suitable Extinguishing Media.

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Use:. Carbon dioxide (CO2). Dry chemical. Foam. Water spray or fog. Cool containers with flooding quantities of water until well after fire is out.

#### Extinguishing media which shall not be used for safety reasons

Do not use straight streams. Do not scatter spilled material with high pressure water streams.

## Specific hazards arising from the chemical

Thermal decomposition can lead to release of irritating gases and vapors. In the event of fire and/or explosion do not breathe fumes. The product is insoluble and floats on water.

#### Hazardous decomposition products

Carbon monoxide (CO), carbon dioxide (CO2)

## Advice for firefighters

#### Special protective equipment for fire-fighters

Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear

Hazchem code

Not listed.

# **SECTION 6: ACCIDENTAL RELEASE MEASURES**

#### Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Ensure adequate ventilation. Use personal protective equipment. Avoid contact with skin, eyes and clothing. Wash thoroughly after handling. Take precautionary measures against static discharges.

Advice for non-emergency	Extremely slippery when spilled.	
personnel		

Advice for emergency responders Use personal protection recommended in Section 8.

#### Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.

#### Methods and material for containment and cleaning up

#### Dike to collect large liquid spills

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Take up mechanically and collect in suitable container for disposal. Clean contaminated objects and areas thoroughly observing environmental regulations.

## Reference to other sections

See Section 8/12/13 for additional information

# SECTION 7: HANDLING AND STORAGE

#### Precautions for safe handling

Ensure adequate ventilation. Do not eat, drink or smoke when using this product. Handle in accordance with good industrial hygiene and safety practice. Keep away from open flames, hot surfaces and sources of ignition. Wash thoroughly after handling. Remove and wash contaminated clothing before re-use.

#### Conditions for safe storage, including any incompatibilities

#### **Technical measures/Storage conditions**

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep cool. Protect from sunlight. Keep away from open flames, hot surfaces and sources of ignition.

#### Incompatible materials

Oxidizing agent

Recommended use

Engine oil

# SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

#### **Control parameters**

#### **Exposure Limits**

Chemical name	Australia	New Zealand	New Zealand - Biological Exposure Indices (BEI)
Highly refined base oil (Viscosity >20.5 cSt @40°C)	TWA: 5 mg/m <sup>3</sup>	TWA: 5 mg/m <sup>3</sup> STEL: 10 mg/m <sup>3</sup>	
Highly refined, low viscosity mineral oils/hydrocarbons (Viscosity >7 - <20.5 cSt @40°C)	TWA: 5 mg/m³	TWA: 5 mg/m <sup>3</sup> STEL: 10 mg/m <sup>3</sup>	

Australia - Workplace Exposure Standards for Airborne Contaminants. New Zealand - Workplace Exposure Standards and Biological Exposure Indices.

#### Appropriate engineering controls

Engineering controls	Ensure adequate ventilation, especially in confined areas.	
Personal protective equipment	Engineering controls should be considered as the first line of protection against adverse exposure to harmful substances, Administrative controls and PPE should be used in the absence of engineering controls or as supplemental controls where engineering controls are insufficient in reducing specific exposures to an acceptable level	
Individual protection measures, such as personal protective equipment		

Eye/face protection	Safety glasses with side-shields.
---------------------	-----------------------------------

Skin and body protection	Long sleeved clothing.
--------------------------	------------------------

#### Hand Protection

Butyl rubber

The following glove type may be suitable for handling this product:. Protective gloves complying with EN 374. Nitrile rubber

Glove thickness => 0.38 mm Break through time => 480 min

Glove thickness => 0.64 mm Break through time => 480 min

Glove material suitability will vary depending on specific use conditions. Consideration should be given to variables such as operational characteristics, anticipated contact time, task requirements and other factors relevant to the selection of PPE. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. Any specific glove information provided is based on published literature and glove manufacturer data. Gloves should be replaced regularly and if there is any sign of damage to the glove material.

Respiratory protection	No special protective equipment required. In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit.
Hygiene measures	Do not eat, drink or smoke when using this product. Handle in accordance with good industrial hygiene and safety practice. Regular cleaning of equipment, work area and clothing is recommended.
Environmental Exposure Controls	Avoid release to the environment.
Thermal hazards	None under normal use conditions

# **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

Information on basic physical and chemical properties

Physical state Odor	Liquid Hydrocarbon-like	Appearance Odor threshold	clear Amber Not Determined
<u>Property</u> pH Melting point / freezing point	<u>Values</u> Not applicable Not determined		<u>Remarks</u>
Initial boiling point and boiling Flash point Evaporation rate Flammability Flammability Limit in Air	g range Not determined 252 °C / 486 °F Not determined Ignitable substance		ASTM D 92
Upper flammability or explose limits	sive Not determined		
Lower flammability or explose limits	sive Not determined		
Vapor pressure Relative vapor density Relative density Solubility(ies) Partition coefficient Autoignition temperature Decomposition temperature	Not Determined Not determined 0.859 @ 15 °C Insoluble in water Not determined Not Determined No data available		
Kinematic viscosity Explosive properties Oxidizing Properties	100.3 cSt @ 40 °C Not applicable Not applicable		ASTM D 445
Other Information			
Viscosity, kinematic (100°C) Pour Point VOC Content (ASTM E-1868-1 VOC content	14.87 cSt @ 100°C -39 °C / -38 °F 0) Not Determined Not Determined		ASTM D 445 ASTM D 97

# **SECTION 10: STABILITY AND REACTIVITY**

**Reactivity** 

None under normal use conditions

#### Chemical stability

Stable under normal conditions.

## Possibility of hazardous reactions

None under normal use conditions

#### Conditions to avoid

Keep away from open flames, hot surfaces and sources of ignition, Extremes of temperature and direct sunlight

#### Incompatible materials

Oxidizing agent

#### Hazardous decomposition products

Carbon monoxide (CO); Thermal decomposition can lead to release of irritating and toxic gases and vapors; Carbon dioxide

# **SECTION 11: TOXICOLOGICAL INFORMATION**

## Information on the likely routes of exposure

Product Information - Principle Ro	outes of Exposure
Inhalation	None known
Eye contact	None known
Skin contact	Repeated or prolonged skin contact may cause allergic reactions with susceptible persons
Ingestion	None known

#### Numerical measures of toxicity - Product Information

ATEmix (oral)	>2000	mg/kg
ATEmix (dermal)	>2000	mg/kg

## Acute toxicity - Product Information

Product does not present an acute toxicity hazard based on known or supplied information.

#### Acute toxicity - Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Highly refined base oil (Viscosity >20.5 cSt @40°C)	>2000 mg/kg	>2000 mg/kg	>5 mg/L
Highly refined, low viscosity mineral oils/hydrocarbons (Viscosity >7 - <20.5 cSt @40°C)	>2000 mg/kg	>2000 mg/kg	>5 mg/L
Phosphorodithioic acid, mixed O,O-bis(sec-Bu and 1,3-dimethylbutyl) esters, zinc salts	2900 - 3400 mg/kg (Rat)	>5000 mg/kg (Rabbit)	

Skin corrosion/irritation	Based on available data, the classification criteria are not met.
Serious eye damage/eye irritation	Based on available data, the classification criteria are not met.
Sensitization Respiratory Sensitization Skin sensitization	Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met. Repeated contact may cause allergic reactions in very susceptible persons.
Germ cell mutagenicity	Based on available data, the classification criteria are not met.
Carcinogenicity	Based on available data, the classification criteria are not met.
Reproductive toxicity	Based on available data, the classification criteria are not met.
STOT - single exposure	Based on available data, the classification criteria are not met
STOT - repeated exposure	Based on available data, the classification criteria are not met
Aspiration hazard	Based on available data, the classification criteria are not met
Other adverse effects	CAS No. 121158-58-5 Contains a known or suspected endocrine disruptor
Exposure levels	See section 8 for more information
Interactive effects	None known

## Delayed and immediate effects as well as chronic effects from short and long-term exposure

# **SECTION 12: ECOLOGICAL INFORMATION**

## **Toxicity**

No special environmental measures are necessary

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Highly refined base oil (Viscosity >20.5 cSt @40°C)	>100: 72 h mg/L EC50	>100: 96 h mg/L LC50		>100: 48 h mg/L EC50
Highly refined, low viscosity mineral oils/hydrocarbons (Viscosity >7 - <20.5 cSt @40°C)	>100: 72 h mg/L EC50	>100: 96 h mg/L LC50		>100: 48 h mg/L EC50
Phosphorodithioic acid, mixed O,O-bis(sec-Bu and 1,3-dimethylbutyl) esters, zinc salts	240 - 410: 72 h Scenedesmus subspicatus mg/L EC50	46: 96 h Cyprinodon variegatus mg/L LC50		1.2: 48 h Daphnia magna mg/L EC50

# Persistence and degradability

The product is not readily biodegradable, but it can be degraded by micro-organisms, it is regarded as being inherently biodegradable.

# **Bioaccumulative potential**

No information available

Chemical name	Partition coefficient
Phosphorodithioic acid, mixed O,O-bis(sec-Bu and 1,3-dimethylbutyl)	4
esters, zinc salts	

#### Mobility in soil

The product is insoluble and floats on water. Is not likely mobile in the environment due its low water solubility.

#### Other adverse effects

Contains a known or suspected endocrine disruptor CAS No. 121158-58-5

# **SECTION 13: DISPOSAL CONSIDERATIONS**

#### Safe handling and disposal methods

Dispose of in accordance with local regulations

## Disposal of any contaminated packaging

Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers. Observe all label precautions until container is cleaned, reconditioned or destroyed.

#### Environmental regulations

Should not be released into the environment

SECTION 14: TRANSPORT INFORMATION		
ADG	Not regulated	
IMDG	Not regulated	
IATA_	Not regulated	
SECTION 15: REGULATORY INFORMATION		

Safety, health and environmental regulations/legislation specific for the substance or mixture

## National regulations

#### Australia

Model Work Health and Safety Regulations (2021). Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice (2020).

#### Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)

No poisons schedule number allocated

### New Zealand

Health and Safety at Work (Hazardous Substances) Regulations 2017.

New Zealand HSNO Approval Number: HSNO Hazard Classification: Not Regulated Not Regulated Not Regulated

#### International Regulations

Ozone-depleting substances (ODS) Not applicable

The Stockholm Convention on Persistent Organic Pollutants Not applicable

The Rotterdam Convention Not applicable

#### International Inventories

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory All ingredients are on the inventory or exempt from listing

**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List All ingredients are on the inventory or exempt from listing

**AICS** - Australian Inventory of Chemical Substances All ingredients are on the inventory or exempt from listing

**PICCS** - Philippines Inventory of Chemicals and Chemical Substances All ingredients are on the inventory or exempt from listing

**KECL** - Korean Existing and Evaluated Chemical Substances All ingredients are on the inventory or exempt from listing

**IECSC** - China Inventory of Existing Chemical Substances Contact supplier for inventory compliance status

 $\ensuremath{\mathsf{ENCS}}$  - Japan Existing and New Chemical Substances All ingredients are on the inventory or exempt from listing

**TCSI** - Taiwan National Existing Chemical Inventory Contact supplier for inventory compliance status

**NZIOC** - New Zealand Inventory of Chemicals All ingredients are on the inventory or exempt from listing

#### **Other Information**

The highly refined base oil (Viscosity >20.5 cSt @40°C) contains one or more substance with the following CAS/EC numbers:

Chemical name	CAS No.	EC No (EU Index No)
Lubricating oils (petroleum), C24-50, solvent-extd.,	101316-72-7	309-877-7
dewaxed, hydrogenated		
Distillates (petroleum), solvent-refined heavy paraffinic	64741-88-4	265-090-8
Distillates (petroleum), solvent-refined light paraffinic	64741-89-5	265-091-3

Residual oils (petroleum), solvent deasphalted	64741-95-3	265-096-0
Distillates (petroleum), solvent-refined heavy naphthenic	64741-96-4	265-097-6
Distillates (petroleum), solvent-refined light naphthenic	64741-97-5	265-098-1
Residual oils (petroleum), solvent-refined	64742-01-4	265-101-6
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	265-155-0
Distillates (petroleum), hydrotreated light naphthenic	64742-53-6	265-156-6
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	265-157-1
Distillates (petroleum), hydrotreated light paraffinic	64742-55-8	265-158-7
Distillates (petroleum), solvent-dewaxed light paraffinic	64742-56-9	265-159-2
Residual oils (petroleum), hydrotreated	64742-57-0	265-160-8
Lubricating oils (petroleum), hydrotreated spent	64742-58-1	265-161-3
Residual oils (petroleum), solvent-dewaxed	64742-62-7	265-166-0
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	265-169-7
Paraffin oils (petroleum), catalytic dewaxed heavy	64742-70-7	265-174-4
Paraffin oils (petroleum), catalytic dewaxed light	64742-71-8	265-176-5
Lubricating oils (petroleum), C>25, hydrotreated bright stock-based	72623-83-7	276-735-8
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, high-viscosity	72623-85-9	276-736-3
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	72623-86-0	276-737-9
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	72623-87-1	276-738-4
Lubricating oils	74869-22-0	278-012-2
White mineral oil (petroleum)	8042-47-5	232-455-8

# The highly refined, low viscosity mineral oils/hydrocarbons (Viscosity >7 - <20.5 cSt @40°C) contains one or more substance with the following CAS/EC numbers:

Chemical name	CAS No.	EC No (EU Index No)
Distillates (petroleum), heavy hydrocracked	64741-76-0	265-077-7
Distillates (petroleum), solvent-refined heavy paraffinic	64741-88-4	265-090-8
Distillates (petroleum), solvent-refined light paraffinic	64741-89-5	265-091-3
Residual oils (petroleum), solvent deasphalted	64741-95-3	265-096-0
Distillates (petroleum), solvent-refined heavy naphthenic	64741-96-4	265-097-6
Distillates (petroleum), solvent-refined light naphthenic	64741-97-5	265-098-1
Residual oils (petroleum), solvent-refined	64742-01-4	265-101-6
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	265-155-0
Distillates (petroleum), hydrotreated light naphthenic	64742-53-6	265-156-6
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	265-157-1
Distillates (petroleum), hydrotreated light paraffinic	64742-55-8	265-158-7
Distillates (petroleum), solvent-dewaxed light paraffinic	64742-56-9	265-159-2
Residual oils (petroleum), hydrotreated	64742-57-0	265-160-8
Lubricating oils (petroleum), hydrotreated spent	64742-58-1	265-161-3
Residual oils (petroleum), solvent-dewaxed	64742-62-7	265-166-0
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	265-169-7
Paraffin oils (petroleum), catalytic dewaxed heavy	64742-70-7	265-174-4
Paraffin oils (petroleum), catalytic dewaxed light	64742-71-8	265-176-5
Dec-1-ene, homopolymer, hydrogenated	68037-01-4	500-183-1
Lubricating oils (petroleum), C>25, hydrotreated bright stock-based	72623-83-7	276-735-8
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, high-viscosity	72623-85-9	276-736-3
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	72623-86-0	276-737-9
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	72623-87-1	276-738-4
Lubricating oils	74869-22-0	278-012-2

Short term exposure limit Skin designation

Carcinogen

# **SECTION 16: OTHER INFORMATION**

Issuing	Date

08-02-2022

Revision Date	08-02-2022
Revision Note	Initial Release

#### Key or legend to abbreviations and acronyms used in the safety data sheet

 TWA
 Time weighted average
 STEL

 Ceiling
 Maximum limit value:
 Sk\*

 +
 Sensitizers
 C

 STOT SE - Specific target organ systemic toxicity (Single exposure)
 STOT RE - Specific target organ systemic toxicity (repeated exposure)

 VOC - Volatile organic compounds
 VOC

#### **Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of Safety Data Sheet**